



HOLLAND INK CORPORATION OF  
AMERICA  
888 V&s Hwy. Hauppauge, NY 11788

**Liquid Cobalt Drier**  
**Material Safety Data Sheet**  
Date 1-1-2012

	H	M	I	S
Hazard Ratings				
Minimal	0	Serious	3	
Slight	1	Severe	4	
Moderate	2			
Health				2
Flammability				1
Reactivity				0

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

DISTRIBUTOR: Van Sol Holland Ink Corporation of America  
888 V&s Hwy. Hauppauge, NY 11788  
Emergency Telephone: 631-715-7000  
Product Class: Printing ink additive  
Trade Name: Van Sol Liquid Cobalt drier

MANUFACTURER: Tower Products Inc.  
2703 Freemansburg Ave.  
Easton, PA 18045  
Chemtrec 24 Hour Emergency No-800-424-9300  
Manufacturer s Code ID: V2163

**2. INGREDIENT COMPOSITION INFORMATION**

Ingredient	CAS No.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Cobalt Tallowate	61789-52-4	40-42	0.1mg/M3	0.1mg/M3	IARC
Heavy Distillate	68476-34-6	9-10	N/A	N/A	No
Glycol Ether	111-77-3	0-1	N/A	N/A	No
Technical White Oil	8042-47-5	40-42	N/A	N/A	No

**3. HAZARDS IDENTIFICATION**

OSHA Hazard Communication 29 CFR 1910.1200 ..... Cobalt Compound

**4. FIRST AID MEASURES**

EFFECTS OF OVEREXPOSURE

Eye Contact Direct contact may cause irritation.  
Skin Contact Prolonged contact or repeated exposure may cause irritation.  
Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages.  
Ingestion May cause gastrointestinal irritation.  
Medical Conditions aggravated by normal exposure Persons with dermatitis should avoid skin contact.  
Target Organs Skin, eyes, lungs, heart, thyroid and pancreas.  
Primary Routes of entry Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

Eye Contact Flush with large amounts of water for at least 20 minutes until irritation subsides. If irritation persists contact a physician.  
Skin Contact Remove contaminated clothing and wash thoroughly before reusing. Wash affected skin areas with soap and water. Seek medical attention if irritation persists.  
Ingestion If swallowed, do not induce vomiting. Call a physician or poison control center.  
Inhalation Remove individual to fresh air.

**5. FIRE FIGHTING MEASURES**

Flash Point ..... Above 250 F Method used: closed cup  
Explosion Limits ..... LEL:1.1 UEL: N/A  
Extinguishing Media ..... Foam, carbon dioxide, dry chemical fire apparatus. Water spray may be applied to cool exposed closed containers.  
Unusual Fire and Explosion Hazards ..... Dense smoke may be generated when burning. Carbon Monoxide and Carbon Dioxide generated as combustion products  
Special Fire Fighting Procedures ..... Self-contained breathing apparatus recommended.

**6. ACCIDENTAL RELEASE MEASURES**

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers for flammable liquids. If petroleum hydrocarbon is used, provide sufficient ventilation.  
Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

**7. HANDLING AND STORAGE**

Handling: Avoid storage above 90 F. Keep containers closed when not in use.  
 Other Precautions: None required.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Ventilation Use sufficient ventilation.	Respiratory Protection None required.
Protective Gloves Impermeable gloves recommended to prevent skin irritation and absorption.	Eye Protection Safety glasses recommended.
	Other Protection None recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Volatile Organic Compounds: (VOCs) .90 lbs./gallon	80 Grams/liter Method 24
Boiling Range °F:> 590-725	Freezing Point °F: N/A
Vapor Density vs. Air: Heavier	Vapor Pressure: less than 0.04 psi
Density: 7.70 lbs./ gallon ASTM D1475	Specific Gravity: 0.92
Type of Odor: Oily hydrocarbon	Odor Threshold: High
Appearance: Purple liquid	pH: N/A
Evaporation Rate vs. Butyl Acetate: Slower	Coefficient of Water/oil Distribution: N/A
Percentage Volatile By Weight: 55% ASTM D2369	

**10. STABILITY AND REACTIVITY**

Product Stability: Stable  
 Conditions to Avoid: Strong oxidizing agents, acids and bases. Avoid storage above 90 F.  
 Keep containers closed when not in use.  
 Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and smoke.  
 Hazardous Polymerization: Will not occur.

**11. TOXICOLOGICAL INFORMATION**

Carcinogen ..... Contains no materials that are considered carcinogenic by National Toxicology Program (NTP), or OSHA. International Agency for Research on Cancer (IARC) has classified Cobalt Compounds as Group 2B Carcinogens. Group 2B Carcinogens are possibly carcinogenic to humans.  
 Mutagen ..... No  
 Teratogen ..... No  
 Reproductive Toxicity No

**12. ECOLOGICAL INFORMATION**

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

**13. DISPOSAL CONSIDERATIONS**

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

**14. TRANSPORT INFORMATION** DOT (HM 181) : Not required  
 Shipping Labels: None required

**15. REGULATORY INFORMATION**

TSCA (Toxic Substance Control Act) ..... All ingredients listed in TSCA Inventory  
 CERCLA Superfund 40CFR 117.302 ..... Contains no reportable materials  
 SARA Title III ..... 40% Cobalt Compound. 0.5% Glycol Ether.  
 FDA ..... This product is not a food additive and would not have approval for direct or indirect contact with food.  
 EINECS (European Economic Community) ..... All ingredients listed.  
 California Proposition 65 ..... None  
 CONEG Legislation ..... Meets all current State and Heavy Metal limitations.  
 Canadian WHMIS ..... Controlled product. Cobalt Drier, Group 2B.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.