

Material Safety Data Sheet

MultiFresh Black Date: 11/30/2006

	н	М	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America 185 Oval Drive Islandia, NY 11749 Emergency Telephone: 631-715-7000 Product Class: Of fset Ink, oxidizing Trade Name: MultiFresh Process Black, MultiFresh Intense Black 2. INGREDIENT COMPOSITION INFORMATION

Ingredient CASNo. ₩Т% OSHA (PEL) ACGIH (TLV) Carcinogen Carbon Black 1333-86-4 15-30 3.5mg/M3 3.5mg/M3 No 2-10 3.5mg/M3 3.5mg/M3 No Organic Pigments Various N/A N/A No Synthetic Resins Various 20-40 Vegetable Oils includes: 8001-Various 8-18 N/A N/A No Linseed Oil 8001-26-1 Soya Oil 8001-22-7 Severe Solvent Refined 64742-13-8 and Acid Treated Middle Distillate 64741-91-9 20-40 N/A N/A No IARC Cobalt Drier 61789-52-4 0-1 0.1mg/M3 N/A Manganese Drier 61788-58-7 0-1 5mg/M3 N/A No Polymeric Wax Blend N/A 2-4 N/A N/A No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200...... Carbon Black and manganese compound

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

	STILLIG OF OVEREMIODORE
Eye ContactDir	ect contact may cause invitation.
Skin ContactPro	longed contact or repeated exposure may cause minor irritation.
InhalationExc	ess inhalation of mist or vapor may cause dizziness, nausea or irritation
of:	nasal and respiratory passages.
IngestionMay	cause gastrointestinal irritation.
Medical Conditions aggravated by norma	l exposure: Persons with dermatitis should avoid skin contat.
Target Organs:Ski	n, eyes, lurgs.
Primary Routes of entryEye	s, inhalation, dennal.
EME	RGENCY FIRST AID PROCEDURES
Eye ContactFlu	sh with large amounts of water until irritation subsides.
fin	itation persists, contact a physician.
Skin Contact:Wa	sh with soap and water. Remove contaminated clothing and wash
the	roughly before reusing.
Ingestion If	swallowed, do not induce vomiting. Call a physician.
InhalationRem	ove individual to fresh air.
5. FIRE FIGHTING MEASURES	

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	-
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient ventilation. W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

HANDLING AND STORAGE 7

Handling: Avoid storage above 90 F. Keep containers closed when not in use. Other Precautions: None required.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use sufficient ventilation.	Eye Protection:	Goggles recommended.
Protective Gloves:	Gloves recommended.	Other Protection:	None recommended.
Respiratory Protection:	None required.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.10 lbs./gallon Boiling Range °F:> 500-590 Vapor Density vs. Air: Heavier 8.78 lbs./ qallon ASTMD1475 Density: Type of Odor: Oily Appearance: Black viscous paste. Evaporation Rate vs. Butyl Acetate: Slower Percentage Volatile By Weight: 25% ASTM D2369

240 Grams/liter Method 24 Freezing Point ^oF: N/A Vapor Pressure: less than 0.04psi Specific Gravity: 1.05 Odor Threshold: High pH: N/A Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability:	Stable
Conditions to Avoid:	Strong oxidizing agents Avoid storage above 90 F.
	Keep containers closed when not in use.
Hazardous Decomposition	Products: None.
Hazardous Polymerization:	Will not actur.

11. TOXICOLOGICAL INFORMATION

Carcinogen	Contains no materials that are considered carcinogenic by OSHA or the
	National Toxicology Program (NIP). International Agency for Research on Cancer (IARC)
	classifies cobalt compounds as 2B carcinogens (possibly carcinogenic to humans)
Mutagen	No
Teratogen	No
Reproductive Toxicity	No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

DISPOSAL CONSIDERATIONS 13.

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

TRANSPORT INFORMATION DOT (HM 181) : Not required Shipping Labels: None required 14.

15. REGULATO RY INFORMATION

TSCA (Toxic Substance Control Act)A CERCLA Superfund 40CFR 117.302C	
SARATile II 1	% cobalt compound and 1% manganese compound
FDA	This printing ink is not a food additive and would not have
approval for	direct or indirect contact with food.
EINECS (European Economic Community) A	ll ingredients listed.
California Proposition 65N	lone
CONEG LegislationM	leets all current State and Heavy Metal limitations.
Canadian WHMISC	antrolled product

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designat ed herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.